Bi-directional deflagration flame arrester
KITO EFA-Def-IIB3-…/…
KITO EFA-Def-IIB3-…/…T





size	DN	ANSI	D1	D2	L1	H	L2	kg
65	25	1“	155	70	294	50	120	
	32	1 ¼“						
100	40	1 ½“	220	106	344	50	145	
	50	2“						
150	50	2“	285	159	404	50	175	
	65	2 ½“						
	80	3“						
200	80	3“	340	206	446	42	200	
	100	4“						
300	100	4“	445	308	586	42	270	
	125	5“						
	150	6“						
400	150	6“	565	388	676	42	315	
	200	8“						
500	200	8“	670	485	806	42	380	
	250	10“						
600	250	10“	780	584	946	42	450	
	300	12“						

Type examination certificate in accordance to ATEX 100 a and EN 12874

CE - marking available

Example for orders :
KITO EFA-Def-IIB3-300/150-T
(flame arrester including temperature sensor)

Dimensions in mm

Design subject to change

Performance curves : H 0.30 N

Standard design

housing	: cast steel 1.0619, 1.4408
gasket	: HD 3822, PTFE
casing for grid	: 1.0305, 1.4571
grid	: 1.4310, 1.4571, strip thickness 0.15 mm
bolts/nuts	: galvanized steel, SS
temperature sensor	: PT 100 (option)
flange connection	: DIN 2501 PN 10 ANSI 150 lbs. RF

Other materials, special designs, heating etc. upon request.

Application

For installation into pipelines to the protection of containers and components against deflagration of flammable liquids and gases.
Approved for all materials of the explosion group IIB3 with a maximum experimental safe gap (MESG) > 0.65 mm.
Preventing flame transmission from both sides in pipelines operating under atmospheric conditions (operating pressure ≤ 1.1 bar abs).
Provided with one or two temperature sensors (PT 100) the flame arrester is safe against short time burning from both or one side. If only one thermal sensor is attached, it must be installed into that part of the body from which a fire is expected.
The distance between the possible ignition source and the flame arrestor must not exceed 50 times the inner pipe diameter.
The installation of the deflagration flame arrester into horizontal and vertical pipelines is permissible.